

PM Fiber Variable Optical Attenuator

产品特点

High precision & Wide attenuation range
 Low Insertion Loss & High PER
 High stability and reliability
 High Power available

应用领域

Optical communication systems test
 Fiber component test
 Fiber Sensor

主要参数

Parameter	Value				
Wavelength (nm)	1310, 1550	1310/1550	1064	980	850
Bandwidth (nm)	±40	±40	±20	±10	±10
Attenuation Range (dB)	0.6~40	0.8~40	0.8~40	0.8~40	1.0~40
Original Loss	≤0.6	≤0.8	≤0.8	≤0.8	≤1.0
Extinction ratio (dB)	≥20				
Return Loss (dB)	≥50				
Fiber Type	Panda Fiber				
Adjustment Precision (dB)	0.02				
Operating Temperature	-5~ +70				
Storage Temperature	-40 ~ + 85				
Dimension (LxMxH) (mm)	26x18x8				

For device with connector, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB lower

订购信息

PMVOA	Wavelength	Pigtail Type	Fiber Type	Length	Connector
	850	900um loose tube 2mm loose tube 3mm loose tube	Panda fiber	0.8m	NE=None
	980				FA=FC/APC
	1064				FC=FC/UPC
	1310				SA=SC/APC
	1550				SC=SC/UPC
	1310/1550				XX=Other

订购详情请联系销售人员