

Dual Window Coupler

产品特点

Wide Bandwidth
Low Insertion Loss
High Reliability

应用领域

Telecommunications
CATV Network
Optical Amplifier

主要参数

Parameter		
Operating wavelength (nm)		1310/1550 or others
Operating bandwidth (nm)		± 40
Typical excess loss (dB)		0.07
Insertion loss (dB)	50/50	≤ 3.6
	40/60	$\leq 4.7/2.7$
	30/70	$\leq 6.0/1.9$
	20/80	$\leq 7.9/1.3$
	10/90	$\leq 11.2/0.75$
	5/95	$\leq 14.6/0.4$
	2/98	$\leq 18.8/0.3$
	1/99	$\leq 22.5/0.25$
PDL (dB)		≤ 0.15
Directivity (dB)		≥ 55
Operating temperature (°C)		40 ~ +85

For device with connector, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB lower. The default connector key is aligned to slow axis.

CP	Port Type	Wavelength (nm)	Coupling Ratio	Pigtail Type	Fiber Type	Length	Connector	Package
	1x2	1310/1550	1/99	250um	SMF-28e	0.8m	NE=None	3x54
	2x2		2/98	900um		other	FA=FC/APC FC=FC/UPC SA=SC/APC SC=SC/UPC LC=LC/UPC XX=Other	3x35
			3/97	2mm				
			3mm				
			50/50					

订购详情请联系销售人员